

213 Series

select	Inquiry	Designation		Dimensions in mm					Weight(kg)	Basic Load Ratings(KN)		Speed(U/min)		Fatigue limit load (kN)
		cylindrical	conical	d	D	B	b	rs min		Dynamic(Cr)	Static(Cor)	Reference speed	Limiting speed	
21305	21305K	25	62	17	5.5	1.1	0.28	41.4	41.5	8500	12000	4.55		
21306	21306K	30	72	19	5.5	1.1	0.41	55.2	61	7500	10000	6.8		
21307	21307K	35	80	21	5.5	1.5	0.55	66.6	72	6700	9500	8.15		
21308	21308K	40	90	23	5.5	1.5	0.705	88	90	7000	9500	11.8		
21309	21309K	45	100	25	5.5	1.5	0.927	102	106	5300	7000	13.7		
21310	21310K	50	110	27	5.5	2	1.21	118	127	5600	7500	18.6		
21311	21311K	55	120	29	5.5	2	1.71	145	163	5600	7500	18.6		
21312	21312K	60	130	31	5.5	2.1	2.1	167	191	4800	6300	26.5		
21313	21313K	65	140	33	5.5	2.1	2.55	194	228	4300	6000	29		
21314	21314K	70	150	35	5.5	2.1	3.18	220	262	3400	4500	34.5		
21315	21315K	75	160	37	5.5	2.1	3.81	239	287	4000	5600	34.5		
21316	21316K	80	170	39	5.5	2.1	4.53	260	315	3800	5300	39		
21317	21317K	85	180	41	5.5	3	5.35	289	355	3800	5300	39		
21318	21318K	90	190	43	8.3	3	6.3	320	400	3400	4500	49		
21320	21320K	100	215	47	8.3	3	8.89	370	465	3400	4500	49		