

S 30 K Series

| select |     | Inquiry Designation |     |      | Dimensions in mm |     |     |     |      |    |    |        |                |           | weight         | Adapter sleeve                   | Locating Ring | Felt                   |            | Cover      |            | This product is available in the following versions |               |
|--------|-----|---------------------|-----|------|------------------|-----|-----|-----|------|----|----|--------|----------------|-----------|----------------|----------------------------------|---------------|------------------------|------------|------------|------------|-----------------------------------------------------|---------------|
|        |     |                     |     |      | d                | E   | H   | A   | b    | C  | H1 | I      | S              | S1        |                |                                  |               |                        |            |            |            | S2                                                  | Fixed bearing |
| S3024K | 110 | 320                 | 112 | 380  | 110              | 40  | 215 | 150 | M 24 | 36 | 30 | 17 kg  | 23024 K/H 3024 | FR 10/180 | 10 x 8,5 - 195 | Dimensions according to DIN 5419 | DK 128        | For closed-end housing | S 3024K AF | S 3024K BF | S 3024K AL | S 3024K BL                                          |               |
| S3026K | 115 | 350                 | 125 | 410  | 120              | 45  | 239 | 160 | M 24 | 36 | 30 | 20 kg  | 23026 K/H 3026 | FR 10/200 | FR 10/200      | Dimensions according to DIN 5419 | DK 133        | For closed-end housing | S 3026K AF | S 3026K BF | S 3026K AL | S 3026K BL                                          |               |
| S3028K | 125 | 350                 | 140 | 410  | 120              | 45  | 260 | 170 | M 24 | 36 | 30 | 25 kg  | 23028 K/H 3028 | FR 10/210 | 14 x 11 - 225  | Dimensions according to DIN 5419 | DK 151        | For closed-end housing | S 3028K AF | S 3028K BF | S 3028K AL | S 3028K BL                                          |               |
| S3030K | 135 | 380                 | 150 | 460  | 130              | 45  | 278 | 180 | M 24 | 36 | 30 | 29 kg  | 23030 K/H 3030 | FR 10/225 | 4 x 11 - 240   | Dimensions according to DIN 5419 | DK 161        | For closed-end housing | S 3030K AF | S 3030K BF | S 3030K AL | S 3030K BL                                          |               |
| S3032K | 140 | 39                  | 150 | 470  | 130              | 50  | 288 | 190 | M 24 | 36 | 30 | 37 kg  | 23032 K/H 3032 | FR 10/240 | 14 x 11 - 250  | Dimensions according to DIN 5419 | DK 166        | For closed-end housing | S 3032K AF | S 3032K BF | S 3032K AL | S 3032K BL                                          |               |
| S3034K | 150 | 450                 | 160 | 540  | 160              | 55  | 320 | 205 | M 30 | 48 | 36 | 45 kg  | 23034 K/H 3034 | FR 10/260 | 16 x 12 - 270  | Dimensions according to DIN 5419 | DK 180        | For closed-end housing | S 3034K AF | S 3034K BF | S 3034K AL | S 3034K BL                                          |               |
| S3036K | 160 | 470                 | 170 | 550  | 160              | 55  | 340 | 210 | M 30 | 48 | 36 | 65 kg  | 23036 K/H 3036 | FR 10/280 | 16 x 12 - 285  | Dimensions according to DIN 5419 | DK 190        | For closed-end housing | S 3036K AF | S 3036K BF | S 3036K AL | S 3036K BL                                          |               |
| S3038K | 170 | 470                 | 170 | 550  | 160              | 55  | 353 | 220 | M 30 | 48 | 36 | 67 kg  | 23038 K/H 3038 | FR 10/290 | 16 x 12 - 300  | Dimensions according to DIN 5419 | DK 200        | For closed-end housing | S 3038K AF | S 3038K BF | S 3038K AL | S 3038K BL                                          |               |
| S3040K | 180 | 515                 | 180 | 610  | 170              | 60  | 373 | 235 | M 30 | 48 | 36 | 72 kg  | 23040 K/H 3040 | FR 10/310 | 16 x 12 - 315  | Dimensions according to DIN 5419 | DK 210        | For closed-end housing | S 3040K AF | S 3040K BF | S 3040K AL | S 3040K BL                                          |               |
| S3044K | 200 | 580                 | 200 | 690  | 190              | 70  | 408 | 255 | M 36 | 50 | 42 | 98 kg  | 23044 K/H 3044 | FR 10/340 | 16 x 12 - 350  | Dimensions according to DIN 5419 | DK 230        | For closed-end housing | S 3044K AF | S 3044K BF | S 3044K AL | S 3044K BL                                          |               |
| S3048K | 220 | 610                 | 210 | 720  | 200              | 75  | 433 | 265 | M 36 | 50 | 42 | 110 kg | 23048 K/H 3048 | FR 10/360 | 16 x 12 - 380  | Dimensions according to DIN 5419 | DK 250        | For closed-end housing | S 3048K AF | S 3048K BF | S 3048K AL | S 3048K BL                                          |               |
| S3052K | 240 | 680                 | 240 | 820  | 220              | 80  | 485 | 285 | M 45 | 70 | 52 | 148 kg | 23052 K/H 3052 | FR 10/400 | 16 x 12 - 410  | Dimensions according to DIN 5419 | DK 270        | For closed-end housing | S 3052K AF | S 3052K BF | S 3052K AL | S 3052K BL                                          |               |
| S3056K | 260 | 720                 | 250 | 860  | 230              | 80  | 505 | 295 | M 45 | 70 | 52 | 165 kg | 23056 K/H 3056 | FR 10/420 | 16 x 12 - 445  | Dimensions according to DIN 5419 | DK 290        | For closed-end housing | S 3056K AF | S 3056K BF | S 3056K AL | S 3056K BL                                          |               |
| S3060K | 280 | 780                 | 280 | 920  | 260              | 90  | 565 | 320 | M 36 | 50 | 42 | 205 kg | 23056 K/H 3060 | FR 10/440 | 16 x 12 - 470  | Dimensions according to DIN 5419 | DK 310        | For closed-end housing | S 3060K AF | S 3060K BF | S 3060K AL | S 3060K BL                                          |               |
| S3064K | 300 | 800                 | 280 | 940  | 260              | 90  | 570 | 320 | M 36 | 50 | 42 | 235 kg | 23064 K/H 3064 | FR 10/460 | 16 x 12 - 505  | Dimensions according to DIN 5419 | DK 330        | For closed-end housing | S 3064K AF | S 3064K BF | S 3064K AL | S 3064K BL                                          |               |
| S3068K | 320 | 860                 | 300 | 1000 | 280              | 95  | 615 | 340 | M 36 | 50 | 42 | 280 kg | 23068 K/H 3068 | FR 10/490 | 16 x 12 - 535  | Dimensions according to DIN 5419 | DK 360        | For closed-end housing | S 3068K AF | S 3068K BF | S 3068K AL | S 3068K BL                                          |               |
| S3072K | 340 | 900                 | 320 | 1060 | 280              | 95  | 655 | 345 | M 36 | 50 | 42 | 340 kg | 23072 K/H 3072 | FR 10/510 | 16 x 12 - 565  | Dimensions according to DIN 5419 | DK 390        | For closed-end housing | S 3072K AF | S 3072K BF | S 3072K AL | S 3072K BL                                          |               |
| S3076K | 360 | 900                 | 330 | 1060 | 280              | 100 | 675 | 380 | M 36 | 50 | 42 | 400 kg | 23076 K/H 3076 | FR 10/530 | 16 x 12 - 600  | Dimensions according to DIN 5419 | DK 410        | For closed-end housing | S 3076K AF | S 3076K BF | S 3076K AL | S 3076K BL                                          |               |
| S3080K | 380 | 950                 | 350 | 1100 | 325              | 120 | 715 | 400 | M 36 | 50 | 42 | 460 kg | 23080 K/H 3080 | FR 10/550 | 16 x 12 - 630  | Dimensions according to DIN 5419 | DK 430        | For closed-end housing | S 3080K AF | S 3080K BF | S 3080K AL | S 3080K BL                                          |               |
| S3084K | 400 | 980                 | 375 | 1160 | 340              | 120 | 750 | 430 | M 36 | 50 | 42 | 500 kg | 23084 K/H 3084 | FR 10/570 | 16 x 12 - 660  | Dimensions according to DIN 5419 | DK 470        | For closed-end housing | S 3084K AF | S 3084K BF | S 3084K AL | S 3084K BL                                          |               |
| S3088K | 410 | 1020                | 390 | 1200 | 340              | 125 | 780 | 430 | M 36 | 50 | 42 | 600 kg | 23088 K/H 3088 | FR 10/590 | 16 x 12 - 675  | Dimensions according to DIN 5419 | DK 490        | For closed-end housing | S 3088K AF | S 3088K BF | S 3088K AL | S 3088K BL                                          |               |
| S3092K | 430 | 1080                | 400 | 1260 | 360              | 130 | 805 | 440 | M 48 | 75 | 56 | 500 kg | 23092 K/H 3092 | FR 10/610 | 16 x 12 - 710  | Dimensions according to DIN 5419 | DK 510        | For closed-end housing | S 3092K AF | S 3092K BF | S 3092K AL | S 3092K BL                                          |               |

S 30 K Series

|        |     |      |     |      |     |     |     |     |      |    |    |        |                |           |               |                                  |        |                        |            |            |            |            |
|--------|-----|------|-----|------|-----|-----|-----|-----|------|----|----|--------|----------------|-----------|---------------|----------------------------------|--------|------------------------|------------|------------|------------|------------|
| S3096K | 450 | 1180 | 410 | 1380 | 380 | 190 | 825 | 440 | M 48 | 75 | 56 | 800 kg | 23096 K/H 3096 | FR 10/630 | 16 x 12 - 740 | Dimensions according to DIN 5419 | DK 530 | For closed-end housing | S 3096K AF | S 3096K BF | S 3096K AL | S 3096K BL |
|--------|-----|------|-----|------|-----|-----|-----|-----|------|----|----|--------|----------------|-----------|---------------|----------------------------------|--------|------------------------|------------|------------|------------|------------|