

GIR...UK / GIL...UK



select	Inquiry	Designation							Dimensions															W	r1s min	Cr	Cor Weight
		Linksgewinde	Right-hand thread	d	D	B	dk	d1	d2	d3	d4	h1	C1	α	l3	l4	l5	l7	d5								
GIR17-UK	GIL17-UK	17 mm	30 mm	14 mm	25 mm	20,7 mm	46 mm	M 16	24 mm	67 mm	11 mm	10°	34 mm	90 mm	10 mm	23 mm	30 mm	27 mm	0,3 mm	22400 N	56500 N	0,22 kg					
GIR12-UK	GIL12-UK	12 mm	22 mm	10 mm	18 mm	14,9 mm	34 mm	M 12	17,5 mm	50 mm	8 mm	11°	23 mm	67 mm	6,5 mm	18 mm	22 mm	19 mm	0,3 mm	11400 N	30400 N	0,096 kg					
GIR30-UK	GIL30-UK	30 mm	47 mm	22 mm	40,7 mm	34,2 mm	73 mm	M30x2	40 mm	110 mm	19 mm	6°	56 mm	146,5 mm	15 mm	37 mm	50 mm	41 mm	0,6 mm	65500 N	138000 N	0,93 kg					
GIR20-UK	GIL20-UK	20 mm	35 mm	16 mm	29 mm	24,1 mm	53 mm	M20x1,5	27,5 mm	77 mm	13 mm	9°	40 mm	103,5 mm	10 mm	27 mm	35 mm	32 mm	0,3 mm	31500 N	75600 N	0,35 kg					
GIR15-UK	GIL15-UK	15 mm	26 mm	12 mm	22 mm	18,4 mm	40 mm	M 14	21 mm	61 mm	10 mm	8°	30 mm	81 mm	8 mm	20 mm	26 mm	22 mm	0,3 mm	17600 N	66800 N	0,18 kg					
GIR10-UK	GIL10-UK	10 mm	19 mm	9 mm	16 mm	13,2 mm	29 mm	M 10	15 mm	43 mm	7 mm	12°	20 mm	57,5 mm	6,5 mm	15 mm	19 mm	17 mm	0,3 mm	8650 N	22000 N	0 061kg					
GIR25-UK	GIL25-UK	25 mm	42 mm	20 mm	35,5 mm	29,3 mm	64 mm	M24x2	33,5 mm	94 mm	17 mm	7°	48 mm	126 mm	12 mm	32 mm	42 mm	36 mm	0,6 mm	51000 N	104000 N	0,64 kg					
GIR70-UK-2RS	GIL70-UK-2RS	70 mm	105 mm	49 mm	92 mm	77,8 mm	160 mm	M56x4	80 mm	200 mm	42 mm	6°	80 mm	280 mm	20 mm	87 mm	98 mm	85 mm	1 mm	885000 N	564000 N	8,6 kg					
GIR50-UK-2RS	GIL50-UK-2RS	50 mm	75 mm	35 mm	66 mm	55,9 mm	112 mm	M45x3	62 mm	160 mm	30 mm	6°	68 mm	216 mm	20 mm	60 mm	75 mm	65 mm	0,6 mm	442000 N	313000 N	3,5 kg					
GIR40-UK-2RS	GIL40-UK-2RS	40 mm	62 mm	28 mm	53 mm	45 mm	92 mm	M39x3	52 mm	142 mm	23 mm	7°	65 mm	188 mm	18 mm	48 mm	65 mm	55 mm	0,6 mm	277000 N	194000 N	2 kg					
GIR80-UK-2RS	GIL80-UK-2RS	80 mm	120 mm	55 mm	105 mm	89,4 mm	180 mm	M64x4	95 mm	230 mm	47 mm	6°	85 mm	320 mm	25 mm	100 mm	110 mm	100 mm	1 mm	1125000 N	689000 N	12 kg					
GIR60-UK-2RS	GIL60-UK-2RS	60 mm	90 mm	44 mm	80 mm	66,8 mm	135 mm	M52x3	70 mm	175 mm	38 mm	6°	70 mm	242,5 mm	20 mm	75 mm	88 mm	75 mm	1 mm	690000 N	485000 N	5,5 kg					
GIR45-UK-2RS	GIL45-UK-2RS	45 mm	68 mm	32 mm	60 mm	50,7 mm	102 mm	M42x3	58 mm	145 mm	27 mm	7°	65 mm	195 mm	20 mm	52 mm	70 mm	60 mm	0,6 mm	360000 N	259000 N	2,5 kg					
GIR35-UK-2RS	GIL35-UK-2RS	35 mm	55 mm	25 mm	47 mm	39,7 mm	82 mm	M36x3	47 mm	125 mm	21 mm	6°	60 mm	166 mm	15 mm	42 mm	58 mm	50 mm	0,6 mm	210000 N	159000 N	1,3 kg					